

Technical Data Sheet

AF-194

Ingredient	Hydroxy compounds, inorganic salts
-------------------	------------------------------------

Warranty	12 months (kept in a cool, dry place at room temperature)
-----------------	---

Applications	AF-194 is used in <ul style="list-style-type: none">● Cement mortar● Drilling mud● Dry mortar● Dry powder coating
---------------------	--

Features	<ul style="list-style-type: none">● Outstanding anti-foaming performance● Good compatibility with the system used
-----------------	--

Physical indicators	
Exterior	white solid powder
pH value	4.0-8.0

Instructions	<ul style="list-style-type: none">● Add directly for use, not suitable for dilution.● Adding amount 0.1%~1%● The optimal addition amount is determined according to the actual situation on site
---------------------	--

Precautions	<ul style="list-style-type: none">● There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water● Storage at room temperature (5-40°C), away from direct sunlight● Refer to the product's Material Safety Data Sheet (MSDS) before use
Usage	<ul style="list-style-type: none">● Not for human injection
restrictions	<ul style="list-style-type: none">● This product is not tested or represented as suitable for medical or pharmaceutical use
Package	<ul style="list-style-type: none">● 15 kg bag

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.