

Technical Data Sheet

AF-501

Ingredient Aqueous emulsion of silicone oil and hydrophobic particles

Warranty 6 months (kept in a cool, dry place at room temperature)

Applications AF-501 is used in

- Polycarboxylate water reducing agent
- Concrete
- Industrial water treatment

Features ● Fast defoaming

- Good compatibility with the system

Physical indicators

Exterior White or slightly yellow milky liquid

Solid content (14-16) %

pH value 6.5-8.5

Viscosity, 25°C 300-8000mPa.s

Instructions ● Shake the product well before use

- This product has very little solubility in water and is soluble in benzene, toluene and mineral oil.
- The addition amount is generally 100~1000ppm. The optimal addition amount will be adjusted according to the actual situation on site.

Precautions

- There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
- Storage at room temperature (5-40°C), away from direct sunlight
- Refer to the product's Material Safety Data Sheet (MSDS) before use

Usage

- Not for human injection

restrictions

- This product is not tested or represented as suitable for medical or pharmaceutical use

Package

- 25kg/200kg plastic drum or 1000kg IBC drum
-

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.