

# Technical Data Sheet

## AF-914

---

**Ingredient**      Silicone oil and hydrophobic particles

---

**Warranty**      6 months (kept in a cool, dry place at room temperature)

---

**Applications**   AF-914 is used in

- Water-based color printing system
- Water-based epoxy system
- Polyvinyl alcohol system

---

**Features**      ● The balance of system compatibility and anti-bubble performance is taken into account.

---

### Physical indicators

**Exterior**      Slightly cloudy liquid

**Solid content**      (>90) %

**pH value**      6.5-8.5

**Viscosity, 25°C**      100~1000mPa.s

---

**Instructions**      ● It is especially suitable for adding at the grinding stage and can be added after pre-dilution with solvent.

---

- 
- The addition amount is generally 0.1~0.6%, and the optimal addition amount is adjusted according to the actual situation on site.
- 

**Precautions**

- There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
  - Storage at room temperature (5-40°C), away from direct sunlight
  - Refer to the product' s Material Safety Data Sheet (MSDS) before use
- 

**Usage**

- Not for human injection

**restrictions**

- This product is not tested or represented as suitable for medical or pharmaceutical use
- 

**Package**

- 25kg/200kg plastic drum or 1000kg IBC drum
- 

**LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY**

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.